



- ✓ **Quality Built**
Built by certified technicians
- ✓ **Quality Control**
LED colour batches are identified for large production runs
- ✓ **Easy Graphic Replacement**
Interchangeable printed translucent film
- ✓ **Ventilation Technology**
All components are engineered with heat sink technology
- ✓ **LED Longevity**
A lifespan of up to 70,000 hours
- ✓ **Even Light Distribution**
Our proprietary light diffusing technology (Edge-Lit) and engineered calculations (Back-Lit) guarantees a uniform displacement on all products



APPLICATIONS

Standard	Indoor usage
Signage	Frame system, POP display, Light boxes, Display stands, Hanging signage/box
Display	Retail fixtures, Kiosk systems, Trade shows, Custom interiors
Architectural	Large format walls, Overhead lighting fixture, Suspended lighting fixture

PROFILE

Extrusion	Solid aluminum construction
Backer	Metal
Standard Profile Edge-Lit Depth	1.25" and 2.375"
Standard Profile Back-Lit Depth	3.5"
Face Material	Lexan, acrylic, Pet G .030 and .060
Power Options	Adapter/transformer, hardwire ready options

OPTIONS

Maximum Dimension	Customized to fit	Frame Colours	Anodized, black, white, custom
Lighting Options	LED Edge-lit or LED Back-lit	Side Options	Single sided or double sided
LED Colours	3200K, 4100K, 5400K, 6500K	Installation Support	Wall mounted, leaning, custom
Intensity	General, high, super		