



- ✓ **Quality Built**
Built by certified technicians
- ✓ **Slim Profile**
Sleek design elements to allow for versatile applications
- ✓ **Quality Control**
LED colour batches are identified for large production runs
- ✓ **Easy Graphic Replacement**
Interchangeable printed translucent film
- ✓ **Ventilation Technology**
All components are engineered with heat sink technology
- ✓ **LED Longevity**
A lifespan of up to 70,000
- ✓ **Even Light Distribution**
Our Proprietary light diffusing technology guarantees uniform light distribution



APPLICATIONS

Standard	Indoor usage
Signage	Frame system, POP display, Light boxes, Display stands, Hanging signage/box
Display	Retail fixtures, Kiosk systems, Trade shows, Custom interiors
Architectural	Large format walls, Overhead lighting fixture, Suspended lighting fixture
Retro Fit	Existing application

PROFILE

Extrusion	Solid Aluminum construction with panel rigidity
Surround Extrusion	Aluminum frame magnetically holds graphic
Standard Profile Depth	0.0875"
Frame Face	0.75"
Face Material	Clear Pet G
Power Options	Adapter/transformer, hardwire ready options

OPTIONS

Maximum Dimension	Customized to fit	Frame Colours	Anodized, black, white, custom
Lighting Options	LED Edge-lit	Side Options	Single sided
LED Colours	3200K, 4100K, 5400K, 6500K	Installation Support	Wall mount or leaning
Intensity	General, high, super	Customize	Size, shape, colour, application